

Y-type Angle Seat Valve

100 Series Threaded Angle Seat Valve



100 Series Welded Angle Seat Valve




100 Series Tri-clamp Angle Seat Valve



100 Series Flanged Angle Seat Valve with Round Bonnet



100 Series Flanged Angle Seat Valve with Square Bonnet



Function Principle

Valve stays closed(open) by spring force in its normal state. When piston is actuated by compressed air, valve becomes opened (closed). For double acting type, valve is opened and closed by compressed air.

Advantages

1. Large flux, low resistance, prevent water-hammer.
2. Y-type raises flux by 30% and make flow more smooth.
3. Long working life.
4. The stem adjusts and lubricates itself automatically, minimizing needs for maintaince.
5. The stainless steel actuator can be rotated 360° for flexiable uses.



Applications

- Brewery
- Textile dyeing
- Air separation
- Pharmaceutical
- Filling machines
- Chemical
- Sterilization
- EPS molding
- Environmental equipments
- Others

Technical Specification

- Operating pressure: 0–16bar (0–232psi)
- Control pressure: 3–8bar (43.5–116psi)
- Control fluid: Neutral gas, Air
- Body material: CF8M/CF8
- Seal material: PTFE
- Actuator material: CF8 (40mm–90mm Actuator), AL (125mm Actuator)
- Actuator size: 40mm, 50mm, 63mm, 90mm, 125mm
- Applicable fluid: Water, Alcohol, Oil, Fuel, Steam, Neutral gas or Liquid, Organic solvent, Acid and lye
- Fluid viscosity: Max 600mm²/s
- Fluid temperature: –10°C — +180°C
+25°C — +220°C
- Ambient temperature: –10°C — +80°C
- Control type: Normally closed, Normally open, Double acting
- Connection type: Threaded (BSP, BSPT, NPT), Welded, Flanged, Tri-clamp
- Leakage class: EN 12266 Class A

Y-type Angle Seat Valve





Main Dimension (Threaded Connection)

Size	Actuator (mm)	Q	C	R	K	G	T	A	L	Hexagon
DN8	40	1/8"	50.5	27	112	1/4"	12	124	68	27
	50	1/8"	60	33	125			135		
DN10	40	1/8"	50.5	27	112	3/8"	12	124	68	27
	50	1/8"	60	33	125			135		
DN15	40	1/8"	50.5	27	112	1/2"	15	124	68	27
	50	1/8"	60	33	125			135		
DN20	50	1/8"	60	33	132	3/4"	16	140	75	32
	50	1/8"	60	33	136			150		
DN25	63	1/8"	75	41	162	1"	17	172	90	40
	63	1/8"	75	41	174			190		
DN32	90	1/8"	106	55	223	1 1/4"	21	235	116	50
	63	1/8"	75	41	175			190		
DN40	90	1/8"	106	55	223	1 1/2"	21	235	116	56
	63	1/8"	75	41	183			205		
DN50	90	1/8"	106	55	232	2"	22	250	138	69
	125AL	1/4"	170	85	300			305		
	90	1/8"	106	55	280			275		
DN65 Square bonnet	125AL	1/4"	170	85	330	2 1/2"	26	320	178	85
	125AL	1/4"	170	85	355			340		
DN80 Square bonnet	125AL	1/4"	170	85	355	3"	27	340	210	100

Main Dimension (Welded Connection)

Size	Actuator (mm)	Q	C	R	K	HA	HL	DIN11850-2		DIN11850-3	
								ΦD	S	ΦD	S
DN15	40	1/8"	50.5	27	112	118	70	19	1.5	20	2
	50	1/8"	60	33	125	128					
DN20	50	1/8"	60	33	132	135	82	23	1.5	24	2
	50	1/8"	60	33	136	150					
DN25	63	1/8"	75	41	162	175	100	29	1.5	30	2
	63	1/8"	75	41	174	186					
DN32	90	1/8"	106	55	223	232	125	35	1.5	36	2
	63	1/8"	75	41	175	190					
DN40	90	1/8"	106	55	223	235	130	41	1.5	42	2
	63	1/8"	75	41	183	206					
DN50	90	1/8"	106	55	232	250	155	53	1.5	54	2
	125AL	1/4"	170	85	300	307					
	90	1/8"	106	55	280	320					
DN65 Square bonnet	125AL	1/4"	170	85	330	360	270	70	2	-	-
DN80 Square bonnet	125AL	1/4"	170	85	355	360	284	85	2	-	-

Y-type Angle Seat Valve



Flange specification: DIN2543/DIN2576/EN1092-1/HG20592; ISO/ANSI/DIN/JIS customization available.

Clamp Specification: ISO 2852; customization available.

Main Dimension (Flange Connection)

Size	Actuator (mm)	Q	A	B	L	C	H	φE	n-φF	φM	φN	φP	α
DN15	40	1/8"	135	125	130	2	14	65	4-14	16	45	95	45°
	50		145	140									
DN20	50	1/8"	165	140	150	2	14	75	4-14	19	56	105	45°
DN25	50	1/8"	170	145	160	2	14	85	4-14	26	65	115	45°
	63		190	175									
DN32	63	1/8"	190	188	180	2	16	100	4-18	31	78	140	45°
	90		230	235									
DN40	63	1/8"	206	190	200	3	16	110	4-18	38	84	150	45°
	90		250	240									
DN50	63	1/8"	235	195	230	3	16	125	4-18	49	100	165	45°
	90		277	245									
	125AL	330	310										
DN65 Square bonnet	90	1/8"	330	280	290	3	18	145	4-18	66	120	185	45°
	125AL	375	330										
DN80 Square bonnet	125AL	1/4"	380	355	310	3	20	160	8-18	78	135	200	22.5°
DN100	125AL	1/4"	420	395	350	3	20	180	8-18	96	155	215	22.5°


Main Dimension (Tri-clamp Connection)

Size	Actuator (mm)	Q	A	K	L	φC	φB	φd	φD
DN15	40	1/8"	130	115	80	19	27.5	15	34
	50	1/8"	140	126					
DN20	50	1/8"	158	148	130	25	43.5	19	50.5
DN25	50	1/8"	165	140	130	32	43.5	27	50.5
	63		188	166					
DN32	63	1/8"	200	174	146	37	43.5	31	50.5
	90		245	223					
DN40	63	1/8"	210	175	160	40	56.5	33	64
	90		255	223					
DN50	63	1/8"	221	185	175	53	56.5	45	64
	90		265	235					
	125AL	325	296						
DN65 Square bonnet	90	1/8"	325	280	278	75	83.5	66	91
	125AL	360	330						
DN80 Square bonnet	125AL	1/4"	360	352	290	89	97	78	106

Y-type Angle Seat Valve


Single Acting, Normally Closed (NC)–Enter Above Seat

Size	Thread end	Orifice (mm)	Flow value Kv(m ³ /h)	Actuator (mm)	Differential pressure range P(MPa)	Control pressure (MPa)
DN8	G1/4"	9.5	1.8	28	0–1.0	0.5–0.7
		13	2.2	40	0–1.6	0.3–0.45
DN10	G3/8"	9.5	2	28	0–1.0	0.5–0.7
		13	3.9	40	0–1.6	0.3–0.45
DN15	G1/2"	9.5	2.2	28	0–1.0	0.5–0.7
		13	4.3	40	0–1.6	0.3–0.45
DN20	G3/4"	18	7.6	50	0–1.6	0.3–0.4
DN25	G1"	24	15.8	50	0–1.6	0.3–0.45
		63	0–1.6	0.3–0.35		
DN32	G1 1/4"	31	26.0	63	0–1.6	0.3–0.55
		90	0–1.6	0.3–0.35		
DN40	G1 1/2"	35	32.0	63	0–1.6	0.3–0.65
		90	0–1.6	0.3–0.4		
DN50	G2"	45	52.0	63	0–0.9	0.3–0.7
		90	0–1.6	0.3–0.45		
		125	0–1.6	0.3–0.4		
DN65	G2 1/2"	61	83.2	90	0–1.0	0.3–0.6
DN80	G3"	80	119	125	0–1.6	0.3–0.4
		125	0–1.6	0.3–0.7		




Double Acting, Normally Closed (NC)–Enter Above Seat

Size	Thread end	Orifice (mm)	Flow value Kv(m ³ /h)	Actuator (mm)	Differential pressure range P(MPa)	Control pressure (MPa)
DN8	G1/4"	13	2.2	40	0–1.6	0.3–0.45
				50	0–1.6	0.3–0.35
DN10	G3/8"	13	3.9	40	0–1.6	0.3–0.45
				50	0–1.6	0.3–0.35
DN15	G1/2"	13	4.3	40	0–1.6	0.3–0.45
				50	0–1.6	0.3–0.35
DN20	G3/4"	18	7.6	50	0–1.6	0.3–0.4
DN25	G1"	24	15.8	50	0–1.6	0.3–0.45
				63	0–1.6	0.3–0.35
DN32	G1 1/4"	31	26.0	63	0–1.6	0.3–0.55
				90	0–1.6	0.3–0.35
DN40	G1 1/2"	35	32.0	63	0–1.6	0.3–0.65
				90	0–1.6	0.3–0.4
DN50	G2"	45	52.0	63	0–0.9	0.3–0.7
				90	0–1.6	0.3–0.45
				125	0–1.6	0.3–0.4
DN65	G2 1/2"	61	83.2	90	0–1.0	0.3–0.6
DN80	G3"	80	119	125	0–1.6	0.3–0.4
				125	0–1.2	0.3–0.7




Single Acting, Normally Closed (NC)–Enter Below Seat (Minimize water-hammer)

Size	Thread end	Orifice (mm)	Flow value Kv(m ³ /h)	Actuator (mm)	Differential pressure range P(MPa)	Control pressure (MPa)
DN8	G1/4"	9.5	1.8	28-A	0–1.0	≥0.5
		13	2.2	40-A	0–1.3	≥0.4
DN10	G3/8"	9.5	2	50-A	0–1.4	≥0.45
		13	3.9	28-A	0–1.0	≥0.5
DN15	G1/2"	9.5	2.2	40-A	0–1.3	≥0.4
		13	4.3	50-A	0–1.4	≥0.45
DN20	G3/4"	18	7.6	50-A	0–1.4	≥0.45
DN25	G1"	24	15.8	50-A	0–0.8	≥0.45
				63-A	0–1.3	≥0.5
DN32	G1 1/4"	31	26.0	63-B	0–0.8	≥0.3
				63-A	0–0.6	≥0.5
				90-A	0–1.6	≥0.6
DN40	G1 1/2"	35	32.0	90-B	0–1.3	≥0.45
				63-A	0–0.5	≥0.5
				90-A	0–1.6	≥0.6
DN50	G2"	45	52.0	90-B	0–1.1	≥0.45
				63-A	0–0.2	≥0.5
				90-A	0–1.0	≥0.6
				90-B	0–0.7	≥0.45
				125-A	0–1.6	≥0.55
DN65	G2 1/2"	61	83.2	125-B	0–1.1	≥0.45
				90-A	0–0.5	≥0.6
				90-B	0–0.2	≥0.45
				125-A	0–0.9	≥0.55
				125-B	0–0.6	≥0.45
DN80	G3"	80	119	125-D	0–0.5	≥0.35
				125-A	0–0.5	≥0.55
				125-B	0–0.3	≥0.45
				125-C	0–0.2	≥0.35
DN100	G4"	90	132	125-A	0–0.25	≥0.55



Double Acting, Normally Closed (NC)–Enter Below Seat (Minimize water-hammer)


Size	Thread end	Orifice (mm)	Flow value Kv(m ³ /h)	Actuator (mm)	Differential pressure range P(MPa)	Control pressure (MPa)
DN8	G1/4"	13	2.2	40	0–1.6	≥0.3
				50	0–1.6	≥0.3
DN10	G3/8"	13	3.9	40	0–1.6	≥0.3
				50	0–1.6	≥0.3
DN15	G1/2"	13	4.3	40	0–1.6	≥0.3
				50	0–1.6	≥0.3
DN20	G3/4"	18	7.6	50	0–1.6	≥0.3
DN25	G1"	24	15.8	50	0–1.3	0.3–0.6
				63	0–1.6	0.3–0.4
DN32	G1 1/4"	31	26.0	63	0–1.6	0.3–0.6
				90	0–1.6	0.3–0.4
DN40	G1 1/2"	35	32.0	63	0–1.6	0.3–0.7
				90	0–1.6	0.3–0.5
DN50	G2"	45	52.0	63	0–0.8	0.3–0.75
				90	0–1.6	0.3–0.6
				125	0–1.6	0.3–0.4
DN65	G2 1/2"	61	83.2	90	0–1.1	0.3–0.7
				125	0–1.6	0.3–0.55
DN80	G3"	80	119	125	0–1.6	0.3–0.65
DN100	G4"	90	132	125	0–1.2	0.4–0.5



Y-type Angle Seat Valve


Double Acting Without Spring—Enter Above Seat

Size	Thread end	Orifice (mm)	Flow value Kv(m ³ /h)	Actuator (mm)	Differential pressure range P(MPa)	Control pressure (MPa)
DN8	G1/4"	13	2.2	40	0-1.6	0.3-0.45
				50	0-1.6	0.3-0.35
DN10	G3/8"	13	3.9	40	0-1.6	0.3-0.45
				50	0-1.6	0.3-0.35
DN15	G1/2"	13	4.3	40	0-1.6	0.3-0.45
				50	0-1.6	0.3-0.35
DN20	G3/4"	18	7.6	50	0-1.6	0.3-0.4
DN25	G1"	24	15.8	50	0-1.6	0.3-0.45
				63	0-1.6	0.3-0.35
DN32	G1 1/4"	31	26.0	63	0-1.6	0.3-0.55
				90	0-1.6	0.3-0.4
DN40	G1 1/2"	35	32.0	63	0-1.6	0.3-0.65
				90	0-1.6	0.3-0.4
DN50	G2"	45	52.0	63	0-1.0	0.3-0.7
				90	0-1.6	0.3-0.45
				125	0-1.6	0.3-0.4
DN65	G2 1/2"	61	83.2	90	0-1.0	0.3-0.6
				125	0-1.6	0.3-0.4
DN80	G3"	80	119	125	0-1.2	0.3-0.7




Normally Open(NO)—Enter Above Seat

Size	Thread end	Orifice (mm)	Flow value Kv(m ³ /h)	Actuator (mm)	Differential pressure range P(MPa)	Control pressure (MPa)
DN8	G1/4"	13	2.2	40	0-1.6	≥ 0.3
				50	0-1.6	≥ 0.3
DN10	G3/8"	13	3.9	40	0-1.6	≥ 0.3
				50	0-1.6	≥ 0.3
DN15	G1/2"	13	4.3	40	0-1.6	≥ 0.3
				50	0-1.6	≥ 0.3
DN20	G3/4"	18	7.6	50	0-1.2	≥ 0.3
DN25	G1"	24	15.8	50	0-0.3	≥ 0.3
				63	0-1.6	≥ 0.45
DN32	G1 1/4"	31	26.0	63	0-1.4	≥ 0.45
DN40	G1 1/2"	35	32.0	63	0-1.4	≥ 0.45
DN50	G2"	45	52.0	63	0-0.6	≥ 0.45




Double Acting Without Spring—Enter Below Seat (Minimize water-hammer)

Size	Thread end	Orifice (mm)	Flow value Kv(m ³ /h)	Actuator (mm)	Differential pressure range P(MPa)	Control pressure (MPa)
DN8	G1/4"	13	2.2	40	0-1.6	0.3-0.4
				50	0-1.6	0.3-0.4
DN10	G3/8"	13	3.9	40	0-1.6	0.3-0.4
				50	0-1.6	0.3-0.4
DN15	G1/2"	13	4.3	40	0-1.6	0.3-0.4
				50	0-1.6	0.3-0.4
DN20	G3/4"	18	7.6	50	0-1.6	0.3-0.4
DN25	G1"	24	15.8	50	0-1.6	0.3-0.65
				63	0-1.6	0.3-0.55
DN32	G1 1/4"	31	26.0	63	0-1.6	0.3-0.7
				90	0-1.6	0.3-0.45
DN40	G1 1/2"	35	32.0	63	0-1.2	0.3-0.75
				90	0-1.6	0.3-0.5
DN50	G2"	45	52.0	63	0-0.4	0.3-0.75
				90	0-1.6	0.3-0.6
				125	0-1.6	0.3-0.4
DN65	G2 1/2"	61	83.2	90	0-1.0	0.3-0.75
				125	0-1.6	0.3-0.6
DN80	G3"	80	119	125	0-1.0	0.3-0.7
DN100	G4"	90	132	125	0-0.8	0.3-0.75



Normally Open(NO)—Enter Below Seat (Minimize water-hammer)

Size	Thread end	Orifice (mm)	Flow value Kv(m ³ /h)	Actuator (mm)	Differential pressure range P(MPa)	Control pressure (MPa)
DN8	G1/4"	13	2.2	40	0-1.6	0.3-0.5
				50	0-1.6	0.3-0.4
DN10	G3/8"	13	3.9	40	0-1.6	0.3-0.5
				50	0-1.6	0.3-0.4
DN15	G1/2"	13	4.3	40	0-1.6	0.3-0.5
				50	0-1.6	0.3-0.4
DN20	G3/4"	18	7.6	50	0-1.6	0.3-0.6
DN25	G1"	24	15.8	50	0-1.3	0.3-0.6
				63	0-1.6	0.3-0.5
DN32	G1 1/4"	31	26.0	63	0-1.3	0.3-0.6
DN40	G1 1/2"	35	32.0	63	0-0.7	0.3-0.6
				90	0-1.6	0.3-0.35
DN50	G2"	45	52.0	63	0-0.5	0.3-0.6
				90	0-1.2	0.3-0.6
				125	0-1.4	0.3-0.7
DN65	G2 1/2"	61	83.2	90	0-0.75	0.3-0.5
DN80	G3"	80	119	125	0-1.2	0.3-0.7



Y-type Angle Seat Valve

Angle Seat Valve with Proximity Switch



Angle Seat Valve with Solenoid Valve



Angle Seat Valve with Manual Override



Angle Seat Valve with Position Indicator





Proximity Switch

Proximity switch can be mounted on angle seat valves of all sizes to monitor and feedback open state of the valve.

Technical Specification

- Operating pressure: 10–30V DC
- Protection class: IP67
- Detection distance: 3mm ± 10% (Customization available)
- Temperature range: -25°C — +70°C
- Enclosure material: brass nickel plating
- Probe material: ABS
- Leakage class: DIN EN 12266 Class A

Output signal



Solenoid Valve

Apply to angle seat valve with any aperture size. Connect to 5/2 or 3/2 way solenoid valve.

Technical Specification

- Applicable Medium: Air (Filtered by 40µm mesh)
- Protection level: IP65
- Connection type: G1/8"
- Power: 24V DC or 220V AC
- Air pressure: 1.5–8bar (22–116psi)
- Temperature range: -5°C — +50°C
- Leakage class: DIN EN 12266 Class A

Manual Override

Can adjust piston position, restrict travel, and regulate flow. Applicable to all types of angle seat valves. Can be used for emergency control, in case of lack of control fluids or electrical/mechanical failure.

Technical Specification


- Handwheel material: die-casted Aluminum
- Control type: Normally closed
- Leakage class: DIN EN 12266 Class A
- Suitable for 40/50/63/90mm actuator

Position Indicator

Position Indicator can be mounted on angle seat valves of all sizes to monitor and feedback both open and close states of the valve.

Technical Specification

- Operating pressure: 12V DC — 36V DC
- Current: 25mA/24V DC
- Indicator: visually signal valve open/close state
- Temperature range: -10°C — +80°C
- Protection level: IP65
- Explosion-proof: Ex nA IIC T4
- Shell material: PA6+PC
- Wiring instruction: open clear lid, thread the cord through opening and connect to desired ports.
- Leakage class: DIN EN 12266 Class A



Y-type Angle Seat Valve

Order Instruction

